

stretchwrapmachines



OR1000 - ORBITWRAP STRETCH WRAP MACHINE

Technical data

- Power voltage: 240V Single phase
- Speed: 10RPM
- Capacity: 1500kg
- Wrap height: 2m
- Turntable: \varnothing 1520mm - 80mm low profile
- Electronic screen with soft touch control for easy operation
- Front fork relocation slots
- Automatic or manual programs
- Automatic photocell load height detection
- Pause function
- Top and bottom wrap number program
- Adjustable film carriage speeds
- Adjustable turntable speeds
- Inverter for soft start and stop
- Turntable stops in starting position
- Adjustable spring brake tension system
- Ramp for pallet truck access

Options

- Wrap height: 2.5m
- Turntable: \varnothing 1800mm
 \varnothing 2200mm



OR2000 - ORBITWRAP STRETCH WRAP MACHINE

Technical data

- Power voltage: 240V Single phase
- Speed: 10RPM
- Capacity: 1500kg
- Wrap height: 2m
- Turntable: \varnothing 1520mm - 80mm low profile
- Electronic screen with soft touch control for easy operation
- Front fork relocation slots
- Automatic or manual programs
- Automatic photocell load height detection
- Inverter for soft start and stop
- Adjustable turntable speeds
- Adjustable film carriage speeds
- Motorised pre-stretch system up to 250%
- Adjustable film delivery speed controls film lay-on force
- Turntable stops in starting position
- Easy film threading/quick loading
- Safety emergency stop
- Top and bottom wrap number program
- Pause function
- Ramp for pallet truck access

Options

- Wrap height: 2.5m
- Turntable: \varnothing 1800mm
 \varnothing 2200mm

